Silent series

interpreter booths

The highest ISO standards and requirements as requested by users have resulted in the Audipack "Silent Series" interpreter booths. The Silent Series consists of three versions: Silent 6300, Silent 9600 and 9700 series. All versions are fully transportable in optional flightcases.



The Silent Series are

easy and quick to install



- ▲ ISO 4043:2016 (latest version) approved
- ▲ Panoramic view windows
- ▲ Advanced cable management
- Quick installation

For effective interpretation, silence is required.

The best solution is an Audipack interpreter booth.

In developing these booths, Audipack has paid full attention to a number of requirements e.g. flexibility, weight, good looks, high-quality materials, ease of use and durability. The scratch resistant surface combined with anodised aluminium frame, gives an attractive and professional appearance.

The Silent Series are easy and fast to install. One person can do the job.

All elements and panels are interchangeable, so there is no difficulty in adapting the construction to local conditions. Even the door can be placed on any side. The roof elements are connected to each other in the same way as the wall, resulting in a safe and solid construction.

Silent 9600 and 9700 series interpreter booths comply with the ISO 4043:2016 standard. Silent 6300 complies with ISO 4043:1998.

For more information, ask for our Silent Series brochure.



9600 SILENT SERIES, ISO 4043:2016, INTERPRETER BOOTH



Ref.

External dimensions in mm Internal dimensions

Weight incl. safety glass and table Colour exterior

Colour interior

Sound insulation capacity Number of booth parts incl. table

Table dimensions in mm

Ventilation Lights

P4600

W 1682 x D 1682 x H 2041 excl. ventilation

W 1600 x D 1600 x H 2000

210 Kg

Light grey (approx. RAL 7042)

Other colours available on request


Dark grey and white Better than ISO 4043:2016


11


1600 x 500

Ventilation B2, detachable (height: 170 mm)

* Also available with ventilation B and without LED light: P4601















9700 SILENT SERIES, ISO 4043:2016, COMPACT IN TRANSPORT



Ref.

External dimensions in mm Internal dimensions

Weight incl. safety glass and table

Colour exterior

Colour interior

Sound insulation capacity

Number of booth parts incl. table

Table dimensions in mm

Including floor

Ventilation Lights

P4602

W 1682 x D 1682 x H 2041 excl. ventilation

W 1600 x D 1600 x H 2000

210 Kg

Light grey (approx. RAL 7042)

Other colours available on request

Dark grey and white

Better than ISO 4043:2016


16


1600 x 500

Ventilation B2, detachable (height: 170 mm)

* Also available with ventilation B and without LED light: P4603

Silent series sound insulation capacity













6300 SILENT SERIES, ISO 4043:1998



Ref. P1483

External dimensions in mm

Internal dimensions

Weight incl. safety glass and table

Colour

Sound insulation capacity

Number of booth parts incl. table and floor

Table dimensions in mm


Including floor Ventilation


Optional Extension sets to 3 or 4 person booth

 $\ensuremath{^{*}}$ DIN 56924 approved only when the optional double glass is mounted

Other colours available on request WWW.AUDIPACK.CO

Silent series sound insulation capacity - ISO 4043:1998







W 1720 x D 1720 x H 2280 incl. ventilation and adjustable feet

W 1600 x D 1600 x H 2000

Better than ISO 4043:1998 According DIN 56924*


Light grey (approx. RAL 7042)

340 Kg

1600 x 500

Included

yes







9300 SILENT SERIES, 1 PERSON BOOTH

Ref.	P4019
Туре	1 person booth
External dimensions in mm	W 814 x D 1682 x H 2041 excl. ventilation
Weight incl. safety glass and table	150 Kg

ACCESSORIES

FLIGHTCASES

Transport your interpreter booth nice and safe in a Audipack flightcase.





Ref. Suitable for Booth

5604+5887 6300 Set of 2

9600

17495 9300 1 person (P4019) Front loader

8969 9700





P1866